


ARMORED CABLES



JACKETED MC

XHHW-2/EnviroPlus®

600 Volt Copper, LSZH Jacket
4 Conductor, Factory Mutual Group 1



Description:

Four copper conductors, stranded and insulated with heat and moisture resistant, chemically crosslinked polyethylene (*type XHHW-2*), phase identified and cabled together with suitable fillers (*as necessary*) and bare copper ground conductor. Cable core is covered with mylar binder tape and aluminum or galvanized steel interlocked armor with an overall black low smoke, zero halogen, lead-free jacket. **Available with tinned conductors.**

Application:

Suitable for use in hazardous locations: Class I - Div 2, Class II - Div 2.

Standards:

UL1569
ICEA S-95-658/NEMA WC-70
Flame Rated: IEEE 383 (70,000 BTU), IEEE 1202/CSA FT-4,
UL 1685 and UL 1581, Two-Hour Firewall
Temperature Rated at 90°C Wet/Dry, Cold Temperature Rated at -40°C
Sunlight Resistant
Direct Burial (*includes encasement in concrete*)
Color Code: Black and Numbered (*optional color codes available*)
Low Smoke, Zero Halogen Jacket
RoHS Compliant

Part Number	Size (AWG or Kcmil)	Strand (no.)	Insulation Thickness (mils)	Grounding Conductor (AWG)	Diameter Over Armor (in.)	Jacket Thickness (mils)	Approx. Diameter Overall (in.)	Approx. Net Weight Aluminum Armor (lb./1000')	Approx. Net Weight Galvanized Armor (lb./1000')	Ampacity* (30°C ambient) 90°C Wet/Dry
AANH8/4	8	7	45	10	0.79	50	0.89	485	579	55
AANH6/4	6	7	45	8	0.87	50	0.97	663	775	75
AANH4/4	4	7	45	8	0.99	50	1.09	907	1,040	95
AANH3/4	3	7	45	6	1.05	50	1.15	1,099	1,242	115
AANH2/4	2	7	45	6	1.13	50	1.23	1,305	1,452	130
AANH1/4	1	19	55	6	1.33	50	1.43	1,624	1,872	145
AANH1/0/4	1/0	19	55	6	1.43	50	1.53	1,956	2,227	170
AANH2/0/4	2/0	19	55	6	1.51	60	1.63	2,381	2,681	195
AANH3/0/4	3/0	19	55	4	1.65	60	1.77	2,935	3,256	225
AANH4/0/4	4/0	19	55	4	1.79	60	1.91	3,560	3,925	260
AANH250/4	250	37	65	4	1.91	60	2.03	4,209	4,601	290
AANH350/4	350	37	65	3	2.17	60	2.29	5,665	6,118	350
AANH500/4	500	37	65	2	2.45	75	2.60	7,873	8,390	430
AANH600/4	600	61	80	2	2.71	75	2.86	9,377	9,943	475

*Per NEC Table 310.15 (B)(16). Four-conductor ampacity assumes three are hot and one is neutral. NOTE: The data shown is approximate and subject to standard industry tolerances.